

## 1 Identification

- **Product identifier**
- **Trade name: Mipa BC-Mischlack T**
- **Application of the substance / the mixture Paint**
- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

MIPA SE  
Am Oberen Moos 1  
D-84051 Essenbach  
Tel.: +49(0)8703-922-0  
Fax.: +49(0)8703-922-100  
e-mail: sdb-registratur@mipa-paints.com  
www.mipa-paints.com

Fleetwood Products Inc.  
13 American Way Suite 15  
USA - NJ 08884 Spotswood  
Tel.: +1 7324169590  
e.mail: fleet089@hotmail.com

- **Emergency telephone number:**

International: 011 49(0)700 24112112 (MIP)

US: +1 872 5888271 (MIP)

US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS07

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

n-Butyl acetate

2-Methoxy-1-methylethyl acetate

Methyl ethyl ketone

- **Hazard statements**

H226 Flammable liquid and vapor.

H336 May cause drowsiness or dizziness.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 2)

**Trade name: Mipa BC-Mischlack T**

(Contd. of page 1)

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a poison center/doctor if you feel unwell.

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 0  
Fire = 3  
Reactivity = 0

- **HMS-ratings (scale 0 - 4)**



HEALTH 0 Health = 0  
FIRE 3 Fire = 3  
REACTIVITY 0 Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

123-86-4	n-Butyl acetate	50-100%
108-65-6	2-Methoxy-1-methylethyl acetate	10-25%
1330-20-7	Xylene	2.5-<5%
78-93-3	Methyl ethyl ketone	<2.5%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

**Trade name: Mipa BC-Mischlack T**

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

123-86-4	n-Butyl acetate	5 ppm
108-65-6	2-Methoxy-1-methylethyl acetate	50 ppm
1330-20-7	Xylene	130 ppm
78-93-3	Methyl ethyl ketone	200 ppm
100-41-4	Ethylbenzene	33 ppm
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
112945-52-5	Silicon dioxide	18 mg/m <sup>3</sup>
85-44-9	Phthalic anhydride	18 mg/m <sup>3</sup>
108-88-3	Toluene	67 ppm
7447-41-8	lithium chloride	2.3 mg/m <sup>3</sup>

### · PAC-2:

123-86-4	n-Butyl acetate	200 ppm
108-65-6	2-Methoxy-1-methylethyl acetate	1,000 ppm
1330-20-7	Xylene	920* ppm
78-93-3	Methyl ethyl ketone	2700* ppm
100-41-4	Ethylbenzene	1100* ppm
1333-86-4	Carbon black	99 mg/m <sup>3</sup>
112945-52-5	Silicon dioxide	100 mg/m <sup>3</sup>
85-44-9	Phthalic anhydride	56 mg/m <sup>3</sup>
108-88-3	Toluene	560 ppm
7447-41-8	lithium chloride	25 mg/m <sup>3</sup>

### · PAC-3:

123-86-4	n-Butyl acetate	3000* ppm
108-65-6	2-Methoxy-1-methylethyl acetate	5000* ppm
1330-20-7	Xylene	2500* ppm
78-93-3	Methyl ethyl ketone	4000* ppm
100-41-4	Ethylbenzene	1800* ppm
1333-86-4	Carbon black	590 mg/m <sup>3</sup>
112945-52-5	Silicon dioxide	630 mg/m <sup>3</sup>
85-44-9	Phthalic anhydride	10,000 mg/m <sup>3</sup>

(Contd. on page 4)

**Trade name: Mipa BC-Mischlack T**

108-88-3	Toluene	(Contd. of page 3) 3700* ppm
7447-41-8	lithium chloride	150 mg/m <sup>3</sup>

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Use only in well ventilated areas.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**123-86-4 n-Butyl acetate**

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

**108-65-6 2-Methoxy-1-methylethyl acetate**

WEEL	Long-term value: 50 ppm
------	-------------------------

**1330-20-7 Xylene**

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

**78-93-3 Methyl ethyl ketone**

PEL	Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
TLV	Short-term value: 300 ppm Long-term value: 200 ppm BEI

(Contd. on page 5)

**Trade name: Mipa BC-Mischlack T**

(Contd. of page 4)

**· Ingredients with biological limit values:**

**1330-20-7 Xylene**

BEI 1.5 g/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: Methylhippuric acids

**78-93-3 Methyl ethyl ketone**

BEI 2 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Methyl ethyl ketone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· **Breathing equipment:**

Not required.



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Breakthrough time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

Trade name: Mipa BC-Mischlack T

(Contd. of page 5)

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

#### · Appearance:

Form: Fluid  
Color: According to product specification

· Odor: Characteristic

· Odor threshold: Not determined.

· pH-value: Not determined.

#### · Change in condition

Melting point/Melting range: Undetermined.  
Boiling point/Boiling range: 124-128 °C (255.2-262.4 °F)

· Flash point: 23 °C (73.4 °F) (DIN 53213)

· Flammability (solid, gaseous): Flammable.

· Ignition temperature: 315 °C (599 °F) (DIN 51794)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

#### · Explosion limits:

Lower: 1.2 Vol %  
Upper: 10.8 Vol %

· Vapor pressure at 20 °C (68 °F): 10.7 hPa (8 mm Hg)

· Density at 20 °C (68 °F): 0.963 g/cm<sup>3</sup> (8.036 lbs/gal) (DIN 53217)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

#### · Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

#### · Viscosity:

Dynamic: Not determined.  
Kinematic at 20 °C (68 °F): >60 s (ISO 6 mm)

#### · Solvent content:

VOC content: 73.07 %  
704 g/l / 5.9 lb/gal

Solids content (weight-%): 26.9 %

· Other information: No further relevant information available.

## 10 Stability and reactivity

· Reactivity: No further relevant information available.

#### · Chemical stability

#### · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· Possibility of hazardous reactions: No dangerous reactions known.

(Contd. on page 7)

**Trade name: Mipa BC-Mischlack T**

(Contd. of page 6)

- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 123-86-4 n-Butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	Xylene	3
100-41-4	Ethylbenzene	2B
1333-86-4	Carbon black	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

USA

(Contd. on page 8)




**Trade name: Mipa BC-Mischlack T**

(Contd. of page 7)

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

· <b>UN-Number</b>	
· <b>DOT, ADR, IMDG, IATA</b>	UN1263
· <b>UN proper shipping name</b>	
· <b>DOT</b>	Paint
· <b>ADR</b>	UN1263 PAINT
· <b>IMDG, IATA</b>	PAINT
· <b>Transport hazard class(es)</b>	
· <b>DOT</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>ADR</b>	
	
· <b>Class</b>	3 (F1) Flammable liquids
· <b>Label</b>	3
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Packing group</b>	
· <b>DOT, ADR, IMDG, IATA</b>	III
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>Hazard identification number (Kemler code):</b>	30
· <b>EMS Number:</b>	F-E, S-E
· <b>Stowage Category</b>	A

(Contd. on page 9)



**Trade name: Mipa BC-Mischlack T**

(Contd. of page 8)

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**  
· **Limited quantities (LQ)** 5L  
· **Remarks:** ≤ 450 l: -

· **IMDG**  
· **Limited quantities (LQ)** 5L  
· **Remarks:** ≤ 30 l: -

· **UN "Model Regulation":** UN 1263 PAINT, 3, III

### 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 Xylene

100-41-4 Ethylbenzene

85-44-9 Phthalic anhydride

108-88-3 Toluene

· **Hazardous Air Pollutants**

1330-20-7 Xylene

100-41-4 Ethylbenzene

85-44-9 Phthalic anhydride

108-88-3 Toluene

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4 Ethylbenzene

1333-86-4 Carbon black

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 Toluene

· **Cancerogeny categories**

· **EPA (Environmental Protection Agency)**

1330-20-7 Xylene

78-93-3 Methyl ethyl ketone

100-41-4 Ethylbenzene

108-88-3 Toluene

I

I

D

II

(Contd. on page 10)

**Trade name: Mipa BC-Mischlack T**

(Contd. of page 9)

· <b>TLV (Threshold Limit Value)</b>			
1330-20-7	Xylene	A4	2.5-<5%
100-41-4	Ethylbenzene	A3	<1%
1333-86-4	Carbon black	A4	<1%
85-44-9	Phthalic anhydride	A4	<0.1%
108-88-3	Toluene	A4	<0.1%

· <b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>	
1333-86-4	Carbon black

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Warning

· **Hazard-determining components of labeling:**

n-Butyl acetate  
2-Methoxy-1-methylethyl acetate  
Methyl ethyl ketone

· **Hazard statements**

H226 Flammable liquid and vapor.  
H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a poison center/doctor if you feel unwell.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Class	Share in %
NK	50-100

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Contact:**

· **Date of preparation / last revision** 03/01/2023

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organisation  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 11)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/01/2023

Reviewed on 02/28/2023

**Trade name: Mipa BC-Mischlack T**

(Contd. of page 10)

DOT: US Department of Transportation  
IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
BEI: Biological Exposure Limit  
Flammable Liquids 3: Flammable liquids – Category 3  
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3  
· \* **Data compared to the previous version altered.**

USA